

Technical Data Sheet

SMF-00100 Rev A




HP2X6B POWER CABLE

120-00032-00

Rev A

PAGE 1 of 1



Description

UV protected and outdoor rated two 6 AWG conductor power cable for RRU applications. Braided shielding prevents radio interference and enhances electrical protection.

Available Variations

HP2X6B Available by the foot.

Additional Parts

- N/A

Electrical Data

| | |
|------------------------|------------------------------|
| Conductor Size | 6 AWG |
| Conductor Quantity | 2 (1 Pair) |
| Operational DC Voltage | 48V |
| DC Resistance | 0.412 Ohm/1000 ft max @ 20°C |
| Color Code | Black, Red |

Mechanical Data

| | |
|----------------------------|-------------------------------|
| Minimum Bend Radius | 7 inches |
| Diameter Over Jacket | 0.661 in (16.79 mm) (Nominal) |
| Approx. Weight | 0.319 lb/ft |
| Recommended Hanger Spacing | 1.0 m |

Environmental Data

| | |
|-------------------|----------------|
| Temperature Range | |
| Installation | -4°F to 140°F |
| Operation | -22°F to 158°F |
| Storage | -22°F to 158°F |

Packaging

Lengths up to 400' are supplied on 24"x10" wood reel
Lengths over 400' are supplied on 32"x18" wood reel



EUPEN

CABLE USA

5181 110th Ave N, Unit D Clearwater, FL 33760 | 800-419-5100 | www.eupen.us