

Technical Data Sheet




FJS450-00065-XXXY

Document No.

120-00035-00

Rev D

PAGE 1 of 1



Description

Fiber Jumper assembly with 2 single mode fibers, black indoor/outdoor distribution riser cable, XXX foot lengths, both ends terminated with duplexed LC connectors, clipped A/B, B/A polarity.

Available Standard Variations

Part Number	Length	Weight lbs
FJS450-00065-010F	10 Feet	0.13
FJS450-00065-020F	20 Feet	0.25
FJS450-00065-030F	30 Feet	0.37
FJS450-00065-050F	50 Feet	0.61

Optical Data

Fiber Quantity	2
Fiber Type	Single Mode Fiber
Connector Type	Duplex LC (UPC polish)
Polarity	A/B and B/A
Insertion loss	< 0.25 dB (Tested per Telcordia GR-326)
Return loss	< 50 dB @ 1310 and 1550 nm (Tested per Telcordia GR-326)

Mechanical Data

Minimum Bend Radius	2 inches
Diameter Over Jacket	0.173in [4.4mm]
Weight	0.012 lb/ft
Maximum Hanger Spacing	1.0m
Crush Resistance	8.85 lb/in
Tensile Strength	300 lbs (Installation), 90 lbs (Operating)

Environmental Data

Temperature Range	
Operation	-40°F to 158°F
Storage	-40°F to 158°F