

Technical Data Sheet




FJS450-00103-XXXY

Document No.

120-00139-00

Rev A

PAGE 1 of 1



Description

Fiber Jumper assembly with 1 single mode fiber, indoor/outdoor plenum distribution cable, XXX foot lengths, both ends terminated with UPC SC simplex connectors.

Available Standard Variations

Part Number	Length	Weight lbs
-------------	--------	------------

Optical Data

Fiber Quantity	1
Fiber Type	Single Mode Fiber
Connector Type	UPC Simplex SC (UPC polish)
Insertion loss (UPC)	< 0.25 dB (Tested per Telcordia GR-326)
Return loss (UPC)	< -50 dB @ 1310 and 1550 nm (Tested per Telcordia GR-326)

Mechanical Data

Minimum Bend Radius	
Operating	2.9 inches
Installation	3.9 inches
Diameter Over Jacket	0.11in [2.85mm]
Weight	0.006 lb/ft
Crush Resistance	19.0 lb/in
Tensile Strength	22.0 lbs (Installation), 6.70 lbs (Operating)

Environmental Data

Temperature Range	
Operation	-40°F to 158°F
Storage	-40°F to 158°F



EUPEN

CABLE USA

5181 110th Ave N, Unit D Clearwater, FL 33760 | 800-419-5100 | www.eupen.us